



H 1900 DS 1801 M

H 1900 DS 1801 M • Axial pump with three steel pistons and light alloy head. • Low pressure detergent delivery with control from the lance. • Remote controlled AUTOMATIC TOTAL-STOP. • Electric motor with thermal protection. • Vertical working position. • Built-in accessory holder.

STANDARD EQUIPMENT

- Spray gun with 23ft hp hose complete with quick screw coupling. • Lance. • Low/high pressure commutation head, detergent control and adjustable water jet angle.



G 150 X Power

G 150X POWER - TST Remote Total–Stop control shuts down the machine when the water gun is turned off, saving energy. - Axial pump with three stainless steel pistons and a brass head. Made for high efficiency, low noise, low vibration operation. - Two-pole continuous duty electric induction motor (2800 rpm) with thermal cutout. Maintenance free. - Handy lance and water gun mounts.- Thanks to the particular chemical injection system and two tanks fitted to these machines, two different detergents can be delivered in the correct quantities. Delivery of the chemical product can be controlled easily from the lance.

STANDARD EQUIPMENT

Complete with all accessories: - handgrip with heatproof extension; - high pressure hose; - lance with high/low pressure switching head and regulation of jet angle, turbo lance.

Code	Model	Pressure	Water Flow	Motor	Voltage	Detergent tank	Dimensions	Weight
		bar	l/h	rpm	V-Hz	l	LxPxW	kg
IDAF92355	H 1900 DS 1801 M	140	410	2800	240V-50Hz	1	29x28x86	23
IDAF92355	G 150 X Power	150	600	2800	240V-50Hz	3	46x35x93	26