



Vanguard DSHL 1530 M



Performer V3 DS 2660 T

VANGUARD • Delayed Total-Stop (TSR) Control: interrupts operation of the appliance 30" after the water gun is turned off then starts it up again when the gun is turned on, extending the working life of components and saving considerable energy. • In models 1530 M the motor is 1400 rpm. This further improves the working life of the mechanical components. • Practical detergent delivery: thanks to the built-in tank, a handy lance control delivers the detergent at low pressure. • Crank type H.P. pump: high efficiency, mechanical components with low working temperature; low noise; brass head: long working life; ceramic pistons: high resistance to wear. • Handy compartments for housing the water gun and lance and hook for power cable. Can be fitted with hose reel (optional) to have everything within easy reach.

STANDARD EQUIPMENT

• Flexible thanks to the new accessories. New handgrip with "EPT" system and "SWIVEL" joint to prevent hose twisting, 10m H.P. hose with screw couplings, lance with high pressure switching head and regulation of jet angle.

PERFORMER V3

• Delayed Total-Stop (TSR) Control: interrupts operation of the appliance 30" after the water gun is turned off then starts it up again when the gun is turned on, extending the working life of components and saving considerable energy. • New H.P. pumps with brass head and ceramic pistons for a longer working life and high efficiency. • Four-pole (1400 rpm) continuous duty motor with double bearing and thermal cutout. Extends the working life of mechanical components. • Pump-motor connection with flexible coupling for less vibrations, greater reliability and a longer working life for all mechanical components. Pump and motor easy to disconnect for fast maintenance. • Pressure regulation knob enables pressure to be adapted to the various cleaning needs. • Ergonomic single knob for on/off switching and detergent regulation.

STANDARD EQUIPMENT

Flexible thanks to the new accessories. New handgrip with "EPT" system and "SWIVEL" joint to prevent hose twisting, 10m H.P. hose with screw couplings, double 70cm stainless steel lance, H.P. and L.P. nozzles.

Code	Model	Pressure	Water Flow	Motor	Voltage	Detergent tank	Dimensions	Weight
		bar	l/h	rpm	V-Hz	l	LxPxW	kg
IDAF40060	Vanguard DSHL 1530 M	100	720	1400	240V-50Hz	7,5	74x43x81	44
IDAF89948	Performer V3 DS 2660 T	190	900	1400	415V	18	71x40x87	59